

# Gizzard Inspection Table



## Technical data

Inspection capacity	gizzards / hour	12000
Peeling capacity	gizzards / hour	1500
Length	mm	1650
Width	mm	620
Height	mm	1050
Weight	kg	75
Installed power per motor	kW	1.1
Water consumption	m3/hour	0.6



**DUTCH POULTRY TECHNOLOGY B.V.**

Hillegom, The Netherlands

[www.dutch-poultry-tech.com](http://www.dutch-poultry-tech.com)

This information corresponds to the most recent available information at the time of publication. The construction, composition and execution of the product are subject to future modification, without notice. All given figures are indicative estimates. No rights can be derived from this publication.

# Gizzard Inspection Table



## Key Benefits

- The gizzard inspection table is designed to remove the yellow inside lining of gizzards
- When using an automatic gizzard harvester it is recommended to use a gizzard inspection table as a quality control back-up. Insufficiently peeled gizzards may be introduced a second time
- Stainless steel frame and work top with two sets of peeling rollers
- Fitted with emergency stop
- Separate discharge for peeled gizzards and offals
- Inspection capacity: up to 12000 gizzards per hour
- Peeling capacity: up to 1500 gizzards per hour



**DUTCH POULTRY TECHNOLOGY B.V.**

Hillegom, The Netherlands

[www.dutch-poultry-tech.com](http://www.dutch-poultry-tech.com)

This information corresponds to the most recent available information at the time of publication. The construction, composition and execution of the product are subject to future modification, without notice. All given figures are indicative estimates. No rights can be derived from this publication.