

Nylon chain conveyor



Technical data

Model		011.0003 (straight)	11.0004 (curve)
Length	mm	5000 mm (in case of straight type)	
Width	mm	700 (standard - other sizes on customer request)	
(Adjustable) height	mm	according to customer requirements	
Installed power	kW	0.37	



DUTCH POULTRY TECHNOLOGY B.V.
Hillegom, The Netherlands
www.dutch-poultry-tech.com

This information corresponds to the most recent available information at the time of publication. The construction, composition and execution of the product are subject to future modification, without notice. All given figures are indicative estimates. No rights can be derived from this publication.

Nylon chain conveyor



Key Benefits

- Nylon chain conveyor for transporting crates within the live bird handling (arrival) area of a poultry processing plant.
- Straight or 90 degrees curved sections.
- Including drive/tensioning unit.
- Straight sections sold in standard length of 5000 mm per section.
- Standard width 700 mm, other widths available on customer request.
- Height according to customer requirements.
- With leveling feet for stabilization and to adjust the height of the machine.
- Made of stainless steel, food grade nylon and other non-corrosive materials.



DUTCH POULTRY TECHNOLOGY B.V.

Hillegom, The Netherlands

www.dutch-poultry-tech.com

This information corresponds to the most recent available information at the time of publication. The construction, composition and execution of the product are subject to future modification, without notice. All given figures are indicative estimates. No rights can be derived from this publication.